



TYPE:

PROJECT:

QTY:

RGB & RGBW LED strips

Colorful series

AVAILABLE LED:

CODE	RGB5050	RGBW-3000	RGBW-4000	RGBW5050-3000	WPRGBW-4000	COBRGBW
VOLTAGE	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC	24VDC
LED TYPE	5050	3838+2110	3838+2110	5050 single chip	3838+2110	COB
COLOUR TEMP	RGB	RGB-3000k	RGB-4000k	RGB-3000k	RGB-4000k	RGB+3000k
RA	>90	>95	>95	>95	>95	>90
LED QUANTITY	120/M	240/M	240/M	120/M	240/M	784/M
VIEWING ANGLE	120°	120°	120°	120°	120°	120°
COMSUMPTION	5.24w/ft, 17.2w/m	5.85w/ft, 19.2w/M	5.85w/ft, 19.2w/M	5.85w/ft, 19.2w/M	4.57w/ft, 15w/m	6.1w/ft, 20w/M
WORKING TEMPERATURE	-20° to 50°C	-20° to 50°C	-20° to 50°C	-20° to 50°C	-20° to 50°C	-20° to 50°C
CLASS	2	2	2	2		2
CERTIFICATION	UL Listed E479167	UL Listed E479167	UL Listed E479167	UL Listed E479167	UL Listed E479167	UL Listed E485696
IP	IP-20	IP-20	IP-20	IP-20	IP68	IP-20
WIDTH	10mm	10mm	10mm	10mm	12mm W x 6mm H	12mm
CUT INCREMENT	100mm	50mm	50mm	50mm	50mm	72mm

All our linear lights can be dimmable or non-dim depending on the power supply they are paired with and must be used with 24V power supplies sold by linearled.ca.