



TYPE:

PROJECT:

QTY:

SMT-W-24150-4C-A

RGBW (4 channel) dimmable constant voltage, 150w WIFI LED driver



Features

- Controllable with app
- RGBW (4 channel, red/green/blue/white)
- Flicker free PWM output, constant voltage
- Input voltage range 100-277vac
- Protection against short circuit, overloading, and over temperature
- Suitable for dry, damp, and wet location
- Efficiency > 87% / load: 0~100%
- 7-year warranty

SPECIFICATION SHEET



TYPE:

PROJECT:

QTY:

Specifications

Output	DC Voltage	24VDC
	Voltage Accuracy	±5%
	Rated current	6.25Amp total
	Rated power	150W
	Voltage Regulation	±0.5%
	Load Regulation	±1%
Input	Voltage Range	100-277 VAC
	Frequency Range	47~63HZ
	Power Factor (Typ.)	PF≥0.99/110V PF≥0.97/277V
	Full Load Efficiency (Typ.)	>84%
	AC Current (Typ.)	1.25A
	Leakage current	<0.27mA/110VAC; <0.25mA/277VAC
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.
	Over Loading	≤120% shut down o/p voltage, re-power on to recover
	Over temperature	100°C±10°C shut down o/p voltage, automatically recover after cooling.
Environment	Working TEMP.	-40~+60°C
	Working Humidity	20~90%RH, non-condensing
	Storage TEM. Humidity	-40~+80°C, 10~95%RH
	TEMP. coefficient	±0.03%/°C (0~50°C)
	Vibration	10~500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes
Safety & EMC	Safety standards	UL8750+UL1310
	Withstand voltage	I/P-O/P: 3.75KVAC
	Isolation resistance	I/P-O/P: 100MΩ/500VDC/25°C/70%RH
	EMC EMISSION	FCC Part 15 B
	EMC IMMUNITY	Compliance to EN61000-4-2, 3, 4, 5, 6, 11, A light industry level
Others	Weight	1.45Kg
	Size	256*78*47mm (L*W*H)
Notes	1. All parameters NOT specially mentioned are measured at 110VAC, 277VAC input, Rated load and 25°C of ambient temperature. 2. Tolerance: includes set up tolerance, line regulation and load regulation.	